


Issue: November, 2020 Supersedes: June, 2019

**1. Product and Company Identification**

<b>Product Name</b>	Morgan Fuel (Cool Power, Omega, Pro Pattern, Sidewinder, Traxxas) all grades.
<b>Other Product Name(s)</b>	Model car and airplane fuel
<b>Product Use</b>	Fuel for engine in model planes and cars
<b>Manufacturer</b>	Morgan Fuel, LLC 200 West Lee Street Enterprise, Alabama 36330 Information: (334) 347 3525
<b>Emergency Telephone Numbers</b>	(800) 424-9300 (CHEMTREC – US) 703 527 3887 (Outside U.S.)

**2. Hazards Identification**

**Emergency Overview:** Flammable liquid fuel in various colors (see section 9) with alcohol odor. Can irritate skin, eyes and respiratory tract. Harmful or fatal if swallowed. (Contains methyl alcohol.)

<b>OSHA Regulatory Status</b>	Hazardous
<b>WHMIS Regulatory Status</b>	Hazardous
<b>OSHA Classification</b>	Flam. Liquid 2, Acute Tox 3, STOT SE 1
<b>WHMIS Classification</b>	Flam. Liquid 2, Acute Tox 3, STOT SE 1
<b>OSHA/WHMIS Signal Word</b>	DANGER
<b>OSHA/WHMIS Hazard Statements</b>	Highly flammable liquid and vapor. Toxic if swallowed, in contact with skin or if inhaled. Causes damage to eyes and may cause blindness, especially if ingested.
<b>OSHA/WHMIS Precautionary Statements</b>	Keep away from heat, sparks, open flames, sources of static electricity & hot surfaces. – No smoking. Heating may cause and explosion. Keep container tightly closed. Do not get in eyes, on skin or on clothing. Wear eye protection. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Store locked up in a well-ventilated space. Keep cool. If swallowed, immediately call a poison control center or doctor. Dispose of container in accordance with Federal and local regulations.
<b>OSHA/WHMIS Label Symbols</b>	
<b>Other Hazards Not Specified by OSHA/WHMIS</b>	None

\*\* Note: Label designed to meet OSHA & FHSA label requirements and may contain additional phrases.

**Potential Health Effects:**

<b>Skin</b>	Causes irritation and dryness. Contact with bare skin may allow some absorption through the skin with harmful effects similar to ingestion of small quantities.
-------------	---

<b>Eyes</b>	Causes irritation
<b>Ingestions</b>	Harmful if swallowed. May cause blindness (methanol content) and unconsciousness. Ingestion of large quantities may be fatal.
<b>Inhalation</b>	Irritating if inhaled. Can cause sleepiness (narcosis), headache, nausea and dizziness.
<b>Chronic Effects</b>	Chronic overexposure can affect the liver and kidneys. Nitromethane is an NTP suspect carcinogen via inhalation and as an animal carcinogen by IARC..

SDS: October, 2014 of Ingredients found on established carcinogen lists:

<b>Ingredient</b>	<b>NTP Status</b>	<b>IARC Statue</b>	<b>OSHA List</b>
Nitromethane	Anticipated carcinogen	2B –Possibly carcinogenic	-----

### 3. Composition / Information on Ingredients

<b>Chemical Name</b>	<b>CAS #</b>	<b>Wt. %</b>
Nitromethane	75-52-5	See table in section 16*
Methyl alcohol	67-56-1	
Lubricants (not hazardous)	Trade Secret	balance

\* Exact percentages are trade secret

A table of compositions for all products is found in section 16.

### 4. First Aid Measures

<b>Skin</b>	Wash with plenty of soap and water. Remove contaminated clothing and launder before reuse. Get prompt medical attention for irritation or any other symptom.
<b>Eyes</b>	Immediately flush with water for at least 15 minutes lifting the upper and lower eyelids intermittently. Get prompt medical assistance.
<b>Ingestions</b>	Contact a doctor or poison control center immediately. Do not induce vomiting unless directed to do so by a physician. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	Remove to fresh air. Get prompt medical assistance for irritation or any other symptom.
<b>Advice to Physician</b>	Product contains methanol and can cause blindness via systemic toxicity. Ethanol has been used to compete with the metabolic pathway for methanol. Apply protocols for methanol poisoning. Treat other effects symptomatically.

### 5. Fire Fighting Measures

<b>Extinguishing Media:</b>	Dry chemical, alcohol-type foam, carbon dioxide, water spray or fog. Do not use direct water stream as this spread burning liquid.
<b>Fire/Explosion Hazards:</b>	Vapors can travel to a source of ignition and flash back.
<b>Fire Fighting Procedures:</b>	Cool intact containers to prevent rupture from heat.
<b>Flammable Limits:</b>	LEL is 7.1% and UEL is 36% for methanol, 63% for nitromethane component.
<b>Flash Point</b>	40 – 45°F (4.4 – 7.2°C) Closed cup
<b>Auto ignition Temperature:</b>	725°F (385°C)
<b>Hazardous Combustion Products:</b>	Carbon monoxide, carbon dioxide and nitrogen oxides are primary hazardous combustion products. Some organic vapors from lubricants may also be formed.

<b>Sensitivity to Impact:</b>	Impact may rupture containers, spilling flammable liquid.
<b>Sensitivity to Static Discharge:</b>	Liquid may be ignited by static discharges.

## 6. Accidental Release Measures

<b>Personal Precautions:</b>	Remove all sources of ignition. Provide respiratory protection in the absence of properly ventilated area.
<b>Containment:</b>	Product is shipped in small containers. If many containers are broken open, surround area with clay or other non-absorbing material.
<b>Clean Up:</b>	Absorb with dry sand or earth and place into containers for proper disposal.
<b>Notification Requirements:</b>	See section 15. Morgan Fuels do not contain reportable quantities in non-bulk packages.

## 7. Handling and Storage

<b>Handling:</b>	Avoid contact with skin, eyes and clothing, Use with adequate ventilation. Keep away from children.
<b>Storage:</b>	Store in a cool, dry, ventilated place. Protect from physical damage.

## 8. Exposure Controls / Personal Protection

<b>Engineering Controls:</b>	Normal ventilation for closed containers. For liquid transfers, use local exhaust ventilation to keep exposure below established safe levels (see below).
------------------------------	---

### Personal Protective Equipment:

<b>Eyes and Face:</b>	Wear splash goggles to avoid accidental eye contact.
<b>Respiratory:</b>	Not required for properly ventilated areas. Otherwise use a NIOSH approved respirator.
<b>Hands, Arms, and Body:</b>	Rubber or neoprene gloves.

### Exposure Guidelines::

Ingredient	ACGIH TLW	ACGIH STEL	OSHA PEL	OSHAL STEL
Methyl alcohol	200 ppm (skin)	250 ppm	200 ppm	None
Nitromethane	20 ppm	None	100 ppm	None

## 9. Physical and Chemical Properties

<b>Appearance &amp; Physical State</b>	Liquid in various colors: Coolpower - Green      Coolpower Heli – Red      Omega – Pink ProPattern - Green      Sidewinder – Red
<b>Odor:</b>	Alcohol with some unpleasantness
<b>Odor Threshold:</b>	Not established
<b>pH (1% solution)</b>	Not determined (organic mixture)
<b>Specific Gravity:</b>	0.811 – 1.001
<b>Initial Boiling Point &amp; Range:</b>	149°F (65°C)
<b>Melting Point /Freezing Point:</b>	Not determined
<b>Evaporation Rate:</b>	1.4 – 2.1 (vs. n-butyl acetate)
<b>Percent Volatile:</b>	100

<b>Solubility in Water</b>	90%
<b>Vapor Density:</b>	1.1 – 2.1
<b>Vapor Pressure:</b>	27 – 123 mm Hg
<b>Upper/ Lower Flammable Limits:</b>	LEL is 7.1% and UEL is 36% (methanol), 63% (nitromethane)
<b>Flash Point</b>	40 – 45°F (4.4 – 7.2°C) Closed cup
<b>Auto ignition Temperature:</b>	725°F (385°C)
<b>Flammability (solid, gas)</b>	Not applicable
<b>Octanol/water partition coefficient</b>	Not determined
<b>Decomposition temperature</b>	Not determined
<b>Viscosity</b>	Solid – Not applicable

## 10. Stability and Reactivity

<b>Stability:</b>	Normally stable
<b>Conditions to Avoid:</b>	Heat and sources of ignition.
<b>Materials to avoid</b>	Strong oxidizers can ignite product
<b>Polymerization:</b>	Will not occur.
<b>Hazardous Decomposition Products</b>	Carbon dioxide and monoxide. Nitrogen oxides.

## 11. Toxicological Information

<b>Eye:</b>	Methyl Alcohol: Irritant Nitromethane: Mild to moderate irritant
<b>Skin:</b>	Methyl Alcohol: Irritant LD <sub>50</sub> (rabbit) 12,800 mg/kg Nitromethane: Irritant. LD <sub>50</sub> (rabbit) > 2,000 mg/kg
<b>Oral:</b>	Methyl Alcohol: LD <sub>50</sub> 3,000 – 4,000 mg/kg (Pigtail monkey) ; (rat) 5628 mg/kg Nitromethane: LD <sub>50</sub> –(rat) - 940 mg/kg
<b>Inhalation:</b>	Methyl Alcohol: LC <sub>50</sub> (rat) 64,000 ppm/4 hr. Nitromethane: LC <sub>50</sub> (rat) >12.75 mg/L 1 hr.
<b>Chronic:</b>	Methyl Alcohol: Repeated exposures may affect the ocular nerve and eyesight. Nitromethane: Suspect carcinogen (NTP). In an inhalation bioassay, nitromethane caused tumors in mice (male and female) but not in male rats. Listed as an IARC animal carcinogen (2B).

## 12. Ecological Information

<b>Acute ecotoxicity:</b>	These products have not been tested as mixtures
<b>Chronic ecotoxicity:</b>	These products have not been tested as mixtures

## 13. Disposal Considerations

<b>RCRA Status</b>	RCRA Ignitable waste: D001
<b>Disposal Method:</b>	Incineration recommended

## 14. Transportation Considerations

<b>DOT Proper Shipping Name:</b> Domestic limited quantity	Flammable liquids, n.o.s. (methanol and nitromethane) Limited Quantity
<b>DOT Primary Hazard Class / Division:</b>	Class 3 – flammable liquids
<b>DOT UN / NA Number:</b>  Domestic International	UN 1993 UN 1992
<b>DOT Packing Group</b>	II
<b>TDG (Canada)</b>	Flammable liquids, toxic, n.o.s. (methanol and nitromethane)
<b>IMDG (International water)</b>	Flammable liquids, toxic, n.o.s. (methanol and nitromethane)

## 15. Regulatory Information

### UNITED STATES:

#### Toxic Substances Control Act (TSCA)

<b>TSCA Inventory Status:</b>	Listed on TSCA Chemical Inventory
<b>Other TSCA Issues:</b>	None

#### SARA Title III/CERCLA

Ingredients with "Reportable Quantities" (RQs) and/or "Threshold Planning Quantities" (TPQs).

<b>Ingredient</b>	<b>SARA/CERCLA RQ (lb)</b>	<b>SARA EHS TPQ (lb)</b>
Methyl Alcohol	5000	None

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center [(800) 424-8802] and to your Local Emergency Planning Committee.

<b>SARA 311 Hazard Class:</b>	Flam. Liquid 2, Acute Tox 3, STOT SE 1
-------------------------------	--

#### SARA 313 Toxic Chemicals:

The following ingredients are SARA 313 "Toxic Chemicals" and may be subject to annual reporting requirements. CAS numbers and weight percents are found in Section 2.

<b>Ingredient</b>	<b>Comment</b>
Methyl Alcohol	Deminimus level: 1%
Nitromethane	Deminimus level: 1%

#### State Right-To-Know

In addition to the ingredients found in Section 2, the following are listed for state right-to-know purposes.

<b>Ingredient</b>	<b>Weight %</b>	<b>Comment</b>
Methanol	See compositions in section 16	California Proposition 65 Developmental toxicant
Nitromethane		California Proposition 65Carcinogen

<b>Additional Regulatory Information:</b>	None
---	------

### CANADA:

<b>WHMIS Classification:</b>	B2, D1A, D2B
<b>WHMIS Ingredient Disclosure List</b>	Methyl alcohol, nitromethane
<b>DSL Status (Domestic substances list)</b>	All ingredients listed on the DSL

Ingredients for this product also found on the chemical inventories of Australia, China, Korea, Japan and the Philippines.

## 16. Other Information

Product Compositions Table

Product	% Nitromethane	% Methanol
Cool Power FAI Omega FAI	----	80 - 100
Cool Power 5% Omega 5% Omega Contro Line 5%	1 – 5	80 - 100
Cool Power 10% Cool Power MV 10% Cool Power Super "T", Omega 10% Omega Control Line 10% Omega Super "T" Traxxas 10%	5 – 10	80 - 100
Product	% Nitromethane	% Methanol
Cool Power YS Heli 15%, 20% Cool Powerd MV 4-Cycle Cool Power MV Heli 15% Cool Power 15%. 25% Cool Power Jet-15 Cool Power MV 15% Cool Powr 4-Cycle% Cool Power Heli 12.5%, 15%, 20% Cool Power ProPattern 20% Cool Power ProPattern 25% Omega 15% Omega Jet-15 Omega 4-Cycle% Omega Heli 15% Sidewinder Backyard Basher Sidwwinder Pro 16%, 25%, 30% Sidewinder Race Formula 16%, 25%, 30% Sidewinder Stike Team 25%, 30% Sidewinder Strike Team Off-Road 20%, 25% 30% Sidewinder Strike Team On-Road 16%, 20%, 25%, 30% Sidewinder World Champ 30% Traxxas 20%	10 – 30	60 – 80
Cool Power Heli 30% Cool Power Heli 30% LS Cool Power 40% Cool Power ProPattern 30%, 40% Omega 40% Sidewinder Pro 40% Sidewinder Race 40% Sidewinder Strike Tream 40% Traxxas 33%	15 – 40	45 – 70
Sidewinder Race 50%	45 – 70	30 – 60

**Changes from previous version:** . Minor editing of text in section 14.

HNOC = Hazards not otherwise classified.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable and suitable to their circumstances.